

**Certifications Standards**

ASME A112.18.1 / CSA B125.1

CEC**Robinet de bain 2 morceaux avec douchette****Caractéristiques**

- Bec de bain : 27,5 l/min (7.3 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Douchette anti-calcaire facile à nettoyer

Options d'économie d'eau

B04-1249-00-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

CC : Chrome
 KK : Noir mat
 LL : Laiton satiné
 BB : Blanc
 NN : Nickel brossé
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 KM : Noir titane
 GG : Or

FR**2-piece tub filler with hand shower****Features**

- Bath spout: 7.3 gpm (27,5 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Hand shower: max: 1.75 gpm (6,6 l/min) - 80 psi
- Non-conductive brass hand shower
- Easy-to-clean anti-limestone hand shower

Water saving options

B04-1249-00-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

CC: Chrome
 KK: Matte black
 LL: Satin brass
 BB: White
 NN: Brushed nickel
 YY: Polished nickel
 VV: Satin copper
 TT: Venitian bronze
 KM: Black titanium
 GG: Gold

EN