

B05-1010-1PL-xx

REC B05

BARIL



Certifications Standards

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61

CMR248 Approval



Robinet de lavabo monotrou, renvoi inclus

Caractéristiques

- Max : 4,5 l/min (1.2 gpm) - 60 psi**
- Aérateur orientable
- Renvoi à bouton poussoir avec trop-plein inclus
- Compatible avec Capteur sans contact ELE-2001-01-xx

Options d'économie d'eau

- B05-1010-1PL-xx-050 : 0.5 gpm / 1,9 L/min
- B05-1010-1PL-xx-100 : 1.0 gpm / 3,7 L/min

Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

Single-hole lavatory faucet, drain included

Features

- Max: 1.2 gpm (4,5 l/min) - 60 psi**
- Adjustable aerator
- Push-button drain with overflow included
- Compatible with Touchless Sensor ELE-2001-01-xx

Water saving options

- B05-1010-1PL-xx-050 : 0.5 gpm / 1,9 L/min
- B05-1010-1PL-xx-100 : 1.0 gpm / 3,7 L/min

Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

