

**Certifications Standards**

ASME A112.18.1 / CSA B125.1

CMR248 Approval

**Robinet de bain 2 morceaux avec douchette****Caractéristiques**

- 35 l/min (9.2 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Robinet à double paroi limitant la conduction de la chaleur
- Douchette : Max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette anti-calcaire facile à nettoyer

Options d'économie d'eau

B45-1269-00-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

CC : Chrome
 KK : Noir mat
 LL : Laiton satiné
 BB : Blanc
 NN : Nickel brossé
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 GG : Or

FR

2-piece tub filler with hand shower**Features**

- 9.2 gpm (35 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Double-walled faucet limiting heat conduction
- Hand shower : max : 1.75 gpm (6,6 l/min) - 80
- Easy-to-clean anti-limestone hand shower

Water saving options

B45-1269-00-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

CC: Chrome
 KK: Matte black
 LL: Satin brass
 BB: White
 NN: Brushed nickel
 YY: Polished nickel
 VV: Satin copper
 TT: Venitian bronze
 GG: Gold

EN

