

B46-1030-00L-xx

PROFILE B46

BARILCertifications Standards

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61

**Robinet de lavabo monotrou, renvoi non inclus**Caractéristiques

- Max : 4,5 l/min (1.2 gpm) - 60 psi**
- Aérateur orientable en silicone facile à nettoyer
- Manette latérale
- Commandez votre renvoi de lavabo
- Compatible avec Capteur sans contact ELE-2001-01-xx

Options d'économie d'eau

- B46-1030-00L-xx-050 : 0.5 gpm / 1,9 L/min
B46-1030-00L-xx-100 : 1.0 gpm / 3,7 L/min

Finis disponibles

- CC : Chrome
KK : Noir mat
LL : Laiton satiné
BB : Blanc
NN : Nickel brossé
YY : Nickel poli
VV : Cuivre satiné
TT : Bronze vénitien
GG : Or

FR

Single-hole lavatory faucet, drain not includedFeatures

- Max: 1.2 gpm (4,5 l/min) - 60 psi**
- Easy-to-clean adjustable silicone aerator
- Side handle
- Order your lavatory drain
- Compatible with Touchless Sensor ELE-2001-01-xx

Water saving options

- B46-1030-00L-xx-050 : 0.5 gpm / 1,9 L/min
B46-1030-00L-xx-100 : 1.0 gpm / 3,7 L/min

Available finishes

- CC: Chrome
KK: Matte black
LL: Satin brass
BB: White
NN: Brushed nickel
YY: Polished nickel
VV: Satin copper
TT: Venitian bronze
GG: Gold

EN

