



Certifications Standards

ASME A112.18.1 / CSA B125.1

CMR248 Approval



Robinet de bain 2 morceaux avec douchette

Caractéristiques

- Bec de bain : 32 l/min (8.4 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Douchette anti-calcaire facile à nettoyer

Options d'économie d'eau

B66-1249-00-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

CC : Chrome
KK : Noir mat
LL : Laiton satiné
MM : Or ambré
BB : Blanc
NN : Nickel brossé
YY : Nickel poli
VV : Cuivre satiné
TT : Bronze vénitien
KM : Noir titane
GG : Or

FR

2-piece tub filler with hand shower

Features

- Bath spout: 8.4 gpm (32 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Hand shower : max : 1.75 gpm (6,6 l/min) - 80 psi
- Non-conductive brass hand shower
- Easy-to-clean anti-limestone hand shower

Water saving options

B66-1249-00-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

CC: Chrome
KK: Matte black
LL: Satin brass
MM: Warm gold
BB: White
NN: Brushed nickel
YY: Polished nickel
VV: Satin copper
TT: Venitian bronze
KM: Black titanium
GG: Gold

EN

