



Certifications Standards

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61
 CMR248 Approval



Robinet de cuisine monotrou avec douchette rétractable 2 jets

Caractéristiques

- Max : 6,8 l/min (1.8 gpm) - 60 psi
- Douchette 2 jets anti-calcaire en laiton à ancrage automatique
- Boyau à connexion « super swivel »
- Bec pivotant permettant à l'utilisateur d'atteindre toutes les zones de l'évier
- Compatible avec Capteur sans contact ELE-1001-01-xx

Options d'économie d'eau

CUI-9245-02L-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

CC : Chrome
 SS : Acier inoxydable
 KK : Noir mat
 LL : Laiton satiné
 BB : Blanc
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 GG : Or

FR

Single-hole kitchen faucet with 2-function pull-down spray

Features

- Max: 1.8 gpm (6,8 l/min) - 60 psi
- 2-function anti-limestone brass spray with automatic docking
- Super Swivel hose connection
- Swivel spout allowing to reach all areas of the sink
- Compatible with Touchless Sensor ELE-1001-01-xx

Water saving options

CUI-9245-02L-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

CC: Chrome
 SS: Stainless steel
 KK: Matte black
 LL: Satin brass
 BB: White
 YY: Polished nickel
 VV: Satin copper
 TT: Venetian bronze
 GG: Gold

EN

